

ARTCOOL Mirror
DUAL Inverter

WI-FI R32
Google Assistant UVnano™



Deluxe
DUAL Inverter

WI-FI R32
Google Assistant UVnano™



Prestige
DUAL Inverter

WI-FI R32
Google Assistant



Standard Plus
DUAL Inverter

WI-FI R32
Google Assistant



ARTCOOL Gallery
DUAL Inverter

WI-FI R32
Google Assistant



Met Luchtreiniger
DUAL Inverter

DUALCOOL ThinQ™

WI-FI R32
Google Assistant



ARTCOOL Mirror

DUAL Inverter UVnano™



Unit		9k		12k		18k		24k		
Binnendeel		AC09BH.NSJ		AC12BH.NSJ		AC18BH.NSK		AC24BH.NSK		
Capaciteit	Koelen	Min / Nom / Max	kW	0.89 / 2.50 / 3.70	0.89 / 3.50 / 4.04	0.90 / 5.00 / 5.50	0.90 / 6.60 / 7.42			
	Verwarmen +7°C	Min / Nom / Max	kW	0.89 / 3.30 / 4.10	0.89 / 4.00 / 5.10	0.90 / 5.80 / 6.40	0.90 / 7.50 / 8.64			
S.E.E.R.				7.0	6.6	7.0	6.9			
S.C.O.P.		Gemiddeld/Warmer		4.0 / 4.9	4.0 / 4.9	4.3 / 5.3	4.3 / 5.3			
Energie Label		Koelen / Verwarmen		A++ / A+	A++ / A+	A++ / A+	A++ / A+			
Geluidsniveau	Koelen	S/L/M/H	dBA	19/27/35/41	19/27/35/41	31/34/39/44	31/34/42/47			
	Verwarmen	L/M/H	dBA	27/35/41	27/35/41	34/39/44	34/42/47			
Afmetingen				mm	837*308*192	837*308*192	998*345*212	998*345*212		
Netto gewicht				kg	9.9	9.9	12.8	13.5		
Koudemiddel					R32	R32	R32	R32		
Buitendeel		AC09BQ.UA3		AC12BQ.UA3		AC18BQ.UL2		AC24BQ.UL2		
Geluidsniveau	Koelen	Hoog	dBA	48	48	53	54			
	Verwarmen	Hoog	dBA	50	50	55	57			
Afmetingen				mm	717*495*230	717*495*230	770*545*288	870*650*330		

Prestige

DUAL Inverter



Unit		9k		12k	
Binnendeel		F09MT.NSM		F12MT.NSM	
Capaciteit	Koelen	Min / Nom / Max	kW	0.90 / 2.50 / 4.00	0.90 / 3.50 / 4.25
	Verwarmen +7°C	Min / Nom / Max	kW	0.90 / 3.20 / 6.90	0.90 / 4.00 / 7.32
S.E.E.R.				9.4	9.1
S.C.O.P.		Gemiddeld/Warmer		5.1 / 6.60	5.1 / 6.60
Energie Label		Koelen / Verwarmen		A+++ / A+++	A+++ / A+++
Geluidsniveau	Koelen	S/L/M/H	dBA	19/27/35/40	19/27/35/40
	Verwarmen	L/M/H	dBA	27/35/40	27/35/40
Afmetingen				mm	875*295*235
Netto gewicht				kg	11.0
Koudemiddel					R32
Buitendeel		F09MT.U24		F12MT.U24	
Geluidsniveau	Koelen	Hoog	dBA	48	48
	Verwarmen	Hoog	dBA	50	50
Afmetingen				mm	870*650*330

ARTCOOL Gallery

DUAL Inverter



Unit		9k		12k	
Binnendeel		A09FT.NSF		A12FT.NSF	
Capaciteit	Koelen	Min / Nom / Max	kW	0.89 / 2.50 / 3.70	0.89 / 3.50 / 4.04
	Verwarmen +7°C	Min / Nom / Max	kW	0.89 / 3.30 / 4.10	0.89 / 4.00 / 5.10
S.E.E.R.				6.8	6.6
S.C.O.P.		Gemiddeld/Warmer		4.0 / 4.6	4.0 / 4.6
Energie Label		Koelen / Verwarmen		A++ / A+	A++ / A+
Geluidsniveau	Koelen	S/L/M/H	dBA	27/35/39/45	27/35/39/45
	Verwarmen	L/M/H	dBA	35/39/45	35/39/45
Afmetingen				mm	600*600*146
Netto gewicht				kg	14.4
Koudemiddel					R32
Buitendeel		A09FT.UL2		A12FT.UL2	
Geluidsniveau	Koelen	Hoog	dBA	51	51
	Verwarmen	Hoog	dBA	51	51
Afmetingen				mm	770*545*288

Deluxe

DUAL Inverter UVnano™



Unit				9k	12k	18k	24k
Binnendeel				DC09RH.NSJ	DC12RH.NSJ	DC18RH.NSK	DC24RH.NSK
Capaciteit	Koelen	Min / Nom / Max	kW	0.89 / 2.50 / 3.70	0.89 / 3.50 / 4.04	0.90 / 5.00 / 5.50	0.90 / 6.60 / 7.42
	Verwarmen +7°C	Min / Nom / Max	kW	0.89 / 3.20 / 5.00	0.89 / 4.00 / 6.00	0.90 / 5.80 / 6.40	0.90 / 7.50 / 8.64
S.E.E.R.				7.9	7.6	7.0	6.9
S.C.O.P.		Gemiddeld/Warmer		4.6 / 5.4	4.6 / 5.4	4.3 / 5.3	4.3 / 5.3
Energie Label		Koelen / Verwarmen		A++ / A++	A++ / A++	A++ / A+	A++ / A+
Geluidsniveau	Koelen	S/L/M/H	dBA	19/27/37/42	19/27/37/42	31/34/39/44	31/34/42/47
	Verwarmen	L/M/H	dBA	27/37/42	27/37/42	34/39/44	34/42/47
Afmetingen		mm		837*308*189	837*308*189	998*345*210	998*345*210
Netto gewicht		kg		9.1	9.1	11.9	12.7
Koudemiddel				R32	R32	R32	R32
Buitendeel				DC09RQ.UL2	DC12RQ.UL2	DC18RQ.UL2	DC24RQ.U24
Geluidsniveau	Koelen	Hoog	dBA	49	49	53	54
	Verwarmen	Hoog	dBA	51	51	55	57
Afmetingen		mm		770*545*288	770*545*288	770*545*288	870*650*330

Standard Plus

DUAL Inverter



Unit				9k	12k	18k	24k
Binnendeel				PC09SQ.NSJ	PC12SQ.NSJ	PC18SQ.NSK	PC24SQ.NSK
Capaciteit	Koelen	Min / Nom / Max	kW	0.89 / 2.50 / 3.70	0.89 / 3.50 / 4.04	0.90 / 5.00 / 5.50	0.90 / 6.60 / 7.42
	Verwarmen +7°C	Min / Nom / Max	kW	0.89 / 3.30 / 4.10	0.89 / 4.00 / 5.10	0.90 / 5.80 / 6.40	0.90 / 7.50 / 8.64
S.E.E.R.				7.0	6.6	7.0	6.9
S.C.O.P.		Gemiddeld/Warmer		4.0 / 4.9	4.0 / 4.9	4.3 / 5.3	4.3 / 5.3
Energie Label		Koelen / Verwarmen		A++ / A+	A++/A+	A++ / A+	A++ / A+
Geluidsniveau	Koelen	S/L/M/H	dBA	19/27/35/41	19/27/35/41	31/34/39/44	31/34/42/47
	Verwarmen	L/M/H	dBA	27/35/41	27/35/41	34/39/44	34/42/47
Afmetingen		mm		837*308*189	837*308*189	998*345*210	998*345*210
Netto gewicht		kg		8.7	8.7	11.9	12.7
Koudemiddel				R32	R32	R32	R32
Buitendeel				PC09SQ.UA3	PC12SQ.UA3	PC18SQ.UL2	PC24SQ.U24
Geluidsniveau	Koelen	Hoog	dBA	48	48	53	54
	Verwarmen	Hoog	dBA	50	50	55	57
Afmetingen		mm		717*495*230	717*495*230	770*545*288	870*650*330

Met

Luchtreiniger

DUAL Inverter



Unit				9k	12k
Binnendeel				AP09RT.NSJ	AP12RT.NSJ
Capaciteit	Koelen	Min / Nom / Max	kW	0.89 / 2.50 / 3.70	0.89 / 3.50 / 4.00
	Verwarmen +7°C	Min / Nom / Max	kW	0.89 / 3.30 / 4.10	0.89 / 4.00 / 4.70
S.E.E.R.				6.6	6.2
S.C.O.P.		Gemiddeld/Warmer		4.0 / 5.0	4.0 / 5.0
Energie Label		Koelen / Verwarmen		A++ / A+	A++ / A+
Geluidsniveau	Koelen	S/L/M/H	dBA	21/27/35/42	21/27/35/42
	Verwarmen	L/M/H	dBA	30/35/41	30/35/41
Afmetingen		mm		857*348*189	857*348*189
Netto gewicht		kg		9.5	9.5
Koudemiddel				R32	R32
Buitendeel				AP09RT.UA3	AP12RT.UA3
Geluidsniveau	Koelen	Hoog	dBA	48	48
	Verwarmen	Hoog	dBA	50	50
Afmetingen		mm		717*495*230	717*495*230